

The **Best** gets **Better...**

3/K-2 FUEL OIL DE-AERATOR FLOW CONTROL

Combines the best features of today's Oil De-Aerators with a new design for the best de-aerator on the market today!

The 3/K-2 Flow Control II automatic fuel oil de-aerator represents state-of-the-art technology and is manufactured in accordance with all safety regulations and is subject to factory testing.

- Provides superior flow characteristics over earlier and competitive de-aerators.
- A second chamber and a third float double seal the vessel.
- Comes with the industry's highest possible bio-fuel rating: B100.
- TUV tested #V132 2007 V1.
- ~~3~~ **5** year warranty.

#P131-35M

| CATEGORY | 3/K-2 OIL DE-AERATOR FLOW CONTROL II | 3/K-1 ORIGINAL OIL DE-AERATOR FLOW CONTROL | TIGERLOOP |
|-----------------------------|--|--|-----------|
| BIO-DIESEL COMPATIBILITY | B100 | B20 | B5 |
| NUMBER OF FLOATS | 3 | 2 | 2 |
| NUMBER OF CHAMBERS | 2 | 1 | 2 |
| MAXIMUM AMBIENT TEMPERATURE | 140°F | 140°F | 105°F |
| MAXIMUM NOZZLE CAPACITY | 26 GPH | 26 GPH | 20 GPH |
| MAXIMUM FLOW | 58 GPH | 58 GPH | 50 GPH |
| MAXIMUM RETURN CAPACITY | 37 GPH | 37 GPH | 30 GPH |



mitco MFG.